

HXP R 206 W/45C

HXP | Mercury short-arc lamps, long life



Product family benefits

- Very high luminance
- Elliptical reflector for efficient focusing of the light
- Long lamp life

Product family features

- AC operation with square-wave current



April 25, 2024, 01:42:07 HXP R 206 W/45C

Technical data

Electrical data


Lamp wattage	5500 W
Nominal voltage	850 V
Lamp voltage	4885 V ¹⁾
Lamp current	34 A
Type of current	AC
Nominal wattage	20000 W

¹⁾ Initial voltage range

Light technical data

Focal length	45.0 mm

Dimensions & weight



Diameter	670 mm
Length with base excl. base pins/connection	77.00 mm

Lifespan

Lifespan	1000 h
Eliespan	1000 11

Additional product data

To be operated with OSRAM PT VIP EVG

Capabilities

Cooling	Forced
Burning position	p20
Application	Other

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	05-03-2024	
Primary Article Identifier	4008321331472	
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database	No declarable substances contained	

Safety advice

Because of their high luminance, UV radiation and high internal pressure in the hot state HXP lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321331472	HXP R 206 W/45C	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm³	158.00 g
4008321331489	HXP R 206 W/45C	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm³	363.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.