

# HTI 1200 W/SE XS

HTI | Metal halide lamps, single-ended



### Product family benefits

- High luminance
- High luminous efficacy and efficiency







# Product datasheet

#### Technical data


### **Electrical data**

Nominal wattage	1200.00 W
Nominal voltage	95.0 V
Lamp voltage	100 V
Nominal current	1380 A
Lamp current	12.7 A

### Photometrical data

Nominal luminous flux	105000 lm	
Luminance	26000 cd/cm <sup>2</sup>	
Color temperature	5400 K	
Color rendering index Ra	> 90	
Luminous efficacy	85 lm/W	

# **Dimensions & weight**



Diameter	29.0 mm <sup>1)</sup>	
Length	135.0 mm	
Light center length (LCL)	59.0 mm	

 $<sup>^{1)}</sup>$  Bulb including current bar

# Lifespan

Lifespan	750 h

# Additional product data

Base (standard designation)	GY22 <sup>1)</sup>	
Product remark	SE = Single ended/XS = eXtreme Seal (maximum permissible foil temperature 450 °C)	

 $<sup>^{1\!\!\!/}</sup>$  Special GY22 base. The ignition voltage may be applied only to the thin pin

# Product datasheet

# Capabilities

Burning position	Other <sup>1)</sup>
------------------	---------------------

 $<sup>^{1)}\,\</sup>mathrm{Current}\,\mathrm{strap}\,\,\mathrm{underneath}$ 

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 05-03-2024				
Primary Article Identifier 4050300371153				
Candidate List Substance 1	No declarable substances contained			
Declaration No. in SCIP database  No declarable substances contained				


# Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300371153	OSRHTI1200SE	-	-	-

#### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300371153	HTI 1200 W/SE XS	Shipping carton box	305 mm x 82 mm x 115 mm	2.88 dm <sup>3</sup>	249.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.