

## HSR

### Metal halide lamps



#### Areas of application

- Entertainment
- Architainment

#### Product family benefits

- Outer bulb for ease of handling

#### Product family features

- Single-ended lamps similar to HTI lamps



Product family datasheet

Technical data

Product description	Electrical data		Photometrical data			Dimensions & weight	
	Nominal voltage	Nominal current	Nominal luminous flux	Luminance	Color temperature	Diameter	Length
HSR 400 W/60	670 V	69 A	33000 lm	20000 cd/cm <sup>2</sup>	6000 K	230 mm	1100 mm
HSR 575 W/60	950 V	7 A		10000 cd/cm <sup>2</sup>	6000 K	300 mm	1250 mm
HSR 575 W/72	975 V	700 A	49000 lm	10000 cd/cm <sup>2</sup>	7200 K	300 mm	1250 mm

Product description	Light center length (LCL)	Lifespan	Additional product data	Capabilities	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan	Base (standard designation)	Burning position	Date of Declaration
HSR 400 W/60	62.0 mm	1000 h	GX9.5	Other	05-03-2024
HSR 575 W/60	65.0 mm	1000 h	GX9.5	Other	05-03-2024
HSR 575 W/72	65.0 mm	1000 h	GX9.5	Other	05-03-2024

Product description	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
HSR 400 W/60	4050300315942   4008321631503	No declarable substances contained	In work
HSR 575 W/60	4050300941776   4008321625885	No declarable substances contained	In work
HSR 575 W/72	4008321074126   4008321625908   4008321662583	No declarable substances contained	No declarable substances contained

## Product family datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HSR lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions. HSR lamps are not capable of hot restarts.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.