SIRIUS HRI 310 W PRO

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime





© 2024, OSRAM GmbH. All rights reserved.

Technical data

Electrical data

Nominal wattage	310.00 W
Nominal current	5 A
Nominal voltage	70.0 V

Photometrical data

Nominal luminous flux	15500 lm
Color temperature	7650 K
Color rendering index Ra	85

Dimensions & weight

Diameter	58.0 mm
Length	72.0 mm
Arc length	0.9 mm

Lifespan

Lifespan	6000 h

Additional product data

Category	PRO

Capabilities

Working distance	37.4 mm

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172085304 | 4062172169424 | 4062172169455
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

© 2024, OSRAM GmbH. All rights reserved.

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172169424	SIRIUS HRI 310 W PRO	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm^3	178.00 g
4062172169431	SIRIUS HRI 310 W PRO	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm^3	402.00 g
4062172169448	SIRIUS HRI 310 W PRO	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm^3	4501.00 g
4062172169455	SIRIUS HRI 310 W PRO	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm^3	178.00 g
4062172169462	SIRIUS HRI 310 W PRO	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm^3	402.00 g
4062172169479	SIRIUS HRI 310 W PRO	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm^3	4501.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.