

# 64796 2500 W 230 V

Halogen studio lamps, single-ended



## Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

## Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)







# Product datasheet

### Technical data

## **Product information**

Order reference	64796
-----------------	-------


### **Electrical data**

Nominal wattage	250000 W	
Nominal voltage	230 V	
On-mode power	2640.00 W	
Energy consumption in on-mode	2640.0 kWh/1000h	

### Photometrical data

Color rendering index Ra	100
Φuse value refers to luminous flux	360
Correlated color temperature CCT	3172 K
Useful luminous flux (Φuse)	63885 lm
Chromaticity coordinate x	0.425
Chromaticity coordinate y	0.400

# Dimensions & weight



Diameter	350 mm
Length	1750 mm
Light center length (LCL)	90.0 mm
Illuminated field	20.0*19.0 mm <sup>2</sup>
Filament diameter	19.0 mm

# Lifespan

Lifespan	400 h

# Product datasheet

## Additional product data

Base (standard designation)	G22
Lighting technology used	HL

# Capabilities

Burning position	s90

## **Certificates & standards**

## **Country specific categorizations**

ANSI code	Other
LIF	CP/91
Order reference	64796

## Logistical data

EAN 10 of contained light source	4008321653987
----------------------------------	---------------

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration 22-04-2024			
Primary Article Identifier	4050300406428   4008321653987		
Candidate List Substance 1	No declarable substances contained		
Declaration No. in SCIP database	aration No. in SCIP database In work		

## Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300406428	OSRH64796	-	-	-
4050300406428	OSRH64796	-	-	-

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321653987	64796 2500 W 230 V	Folding carton box 1	57 mm x 57 mm x 191 mm	0.62 dm <sup>3</sup>	158.00 g
4008321984302	64796 2500 W 230 V	Shipping carton box 12	249 mm x 189 mm x 216 mm	10.17 dm³	2096.00 g
4050300406428	64796 2500 W 230 V	Folding carton box 1	- x - x -		
4050300406435	64796 2500 W 230 V	Shipping carton box 20	370 mm x 225 mm x 300 mm	24.98 dm³	4328.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

A summary of studio lamps can be found on the halogen studio lamps poster.

For more information on halogen lamps for studio, stage and TV see the brochure:

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

<sup>&</sup>quot;Good news for show business"

<sup>&</sup>quot;Halogen High Voltage Lamps" cross reference list