

# 64678 800 W 230 V

Halogen studio lamps, single-ended



#### Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

#### Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)



April 26, 2024, 18:45:58 64678 800 W 230 V

#### Technical data

#### **Product information**

#### **Electrical data**


Nominal wattage	80000 W	
Nominal voltage	230 V	
On-mode power	835.00 W	
Energy consumption in on-mode	835.0 kWh/1000h	

#### Photometrical data

Color rendering index Ra	100
Φuse value refers to luminous flux	360
Correlated color temperature CCT	3146 К
Useful luminous flux (Фиse)	19415 lm
Chromaticity coordinate x	0.427
Chromaticity coordinate y	0.400

# Dimensions & weight





Diameter	190 mm
Length 1010 mm	
Light center length (LCL)	60.5 mm
Illuminated field	9.0*13.0 mm <sup>2</sup>
Filament diameter	13.0 mm

# Lifespan

Lifespan	250 h

#### Additional product data

Base (standard designation)	G9.5
Lighting technology used	HL

#### Capabilities

Burning position s90	
----------------------	--

#### **Certificates & standards**

Energy efficiency class G	

### **Country specific categorizations**

ANSI code	Other
Order reference	64678 800W 230V

#### Logistical data

EAN 10 of contained light source	4008321624055
----------------------------------	---------------

#### **Environmental information**

#### Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	22-04-2024	
Primary Article Identifier	4050300609102   4008321624055	
Candidate List Substance 1 No declarable substances contained		
Declaration No. in SCIP database In work		

#### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300609102	OSRH64678	-	-	-
4050300609102	OSRH64678	-	-	-

64678 800 W 230 V

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321624055	64678 800 W 230 V	Folding carton box 1	40 mm x 40 mm x 129 mm	0.21 dm³	49.00 g
4008321624062	64678 800 W 230 V	Shipping carton box 12	178 mm x 137 mm x 152 mm	3.71 dm³	644.00 g
4050300609102	64678 800 W 230 V	Folding carton box 1	- x - x -		
4050300609119	64678 800 W 230 V	Shipping carton box 25	245 mm x 165 mm x 245 mm	9.90 dm <sup>3</sup>	1358.33 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

A summary of studio lamps can be found on the halogen studio lamps poster. For more information on halogen lamps for studio, stage and TV see the brochure: "Good news for show business" "Halogen High Voltage Lamps" cross reference list

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.