

64340

Halogen lamps, current-controlled, double-ended




Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

Product family features

- Dimmable
- Infrared radiation output that provides light in the worst of conditions



Product datasheet

Technical data

Product information

Order reference	64340 100W 6.6A
-----------------	-----------------


Electrical data

Lamp current	6.6 A
Nominal wattage	100.00 W

Photometrical data

Luminous intensity	24000 cd
--------------------	----------

Dimensions & weight



Diameter	51.0 mm
Length	65.6 mm
Length with base excl. base pins/connection	65.00 mm

Lifespan

Lifespan	1000 h
----------	--------

Additional product data

Base (standard designation)	R7s
-----------------------------	-----

Capabilities

Burning position	Horizontal
------------------	------------

Country specific categorizations

LIF	J1/82
Order reference	64340 100W 6.6A

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-05-2024
Primary Article Identifier	4050300017266
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300017266	OSRH64340	-	4739724	-
4050300017266	OSRH64340	-	4739724	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300017266	64340	Folding carton box 1	113 mm x 33 mm x 33 mm	0.12 dm ³	19.00 g
4050300209098	64340	Shipping carton box 25	180 mm x 130 mm x 180 mm	4.21 dm ³	510.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on airfield lamps see the brochure:
"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.