

# XBO 5000 W/HBM XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



#### Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

## Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

#### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R<sub>a</sub> >








## Product datasheet

#### Technical data

### **Electrical data**

Nominal current	140 A
Current control range	100150 A
Nominal wattage	500000 W
Nominal voltage	340 V

## **Dimensions & weight**



Diameter	700 mm
Length	4390 mm
Length with base excl. base pins/connection	393.00 mm
Light center length (LCL)	170.5 mm <sup>1)</sup>
Cable/wire length, input side	400 mm
Electrode gap cold	7.5 mm
Product weight	102290 g
Cable length	4000

<sup>1)</sup> Distance from end of base to tip of electrode (cold)

## Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

## Lifespan

Lifespan	1200 h

## Additional product data

Base anode (standard designation)	SFaX30-9.5
Base cathode (standard designation)	SFa30-7.9

## Product datasheet

## Capabilities

Cooling	Forced <sup>1)</sup>
Burning position	p15 <sup>2)</sup>

 $<sup>^{1)}</sup>$  Vertical and horizontal

#### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	05-03-2024		
Primary Article Identifier	4008321334916   4008321412836		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	72c018af-3320-4320-a45d-d7545789b35e		

<sup>2)</sup> For vertical burning position: anode (+) on top

### Product datasheet

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321334916	XBO 5000 W/HBM XL OFR	Shipping carton box 1	590 mm x 234 mm x 229 mm	31.62 dm³	2109.00 g
4008321412836	XBO 5000 W/HBM XL OFR	Shipping carton box	590 mm x 234 mm x 229 mm	31.62 dm³	2021.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.