

XBO 2000 W/HTT OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R_a >








Product datasheet

Technical data

Electrical data

Nominal current	2500 A
Current control range	5085 A
Nominal wattage	200000 W
Nominal voltage	240 V

Dimensions & weight



Diameter	520 mm
Length	3700 mm
Electrode gap cold	5.8 mm
Product weight	56150 g
Cable length	3200

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C	
--	--------	--

Lifespan

Lifespan	2400 h

Additional product data

Base anode (standard designation)	SK27/50		
Base cathode (standard designation)	SFcX27-8		
Product remark	OFR = Ozone-free version/H = Suitable for horizontal burning position/TT = Two threaded pins		

Capabilities

Cooling	Forced

Product datasheet

Burning position	Other ¹⁾
• · ·	

 $^{^{1)}}$ For vertical burning position: anode (+) on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	05-03-2024		
Primary Article Identifier	4008321064769 4008321650443		
Declaration No. in SCIP database	In work		

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321064769	OSRXBO2000HTTOFR	-	-	- -

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321064769	XBO 2000 W/HTT OFR	Shipping carton box	590 mm x 229 mm x 234 mm	31.62 dm³	1647.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.