

HBO 1002 W/CEL

HBO-IC Microlithography lamps for Canon i-line systems | Microlithography lamps for Canon i-line systems




Technical data

Electrical data

Nominal current	16 A
Nominal voltage	470 V
Type of current	DC
Rated wattage	75000 W
Nominal wattage	750.00 ... 1000.00 W

Dimensions & weight



Diameter	280 mm
Length	1750 mm
Mounting length	157.0 mm
Electrode gap cold	3.0 mm

Capabilities

Burning position	Other ¹⁾
------------------	---------------------

¹⁾ Anode underneath

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	15-02-2024
Primary Article Identifier	4050300412634
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	5ec6ff55-9ef7-453c-af73-6d14ad4c8c6b

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300412634	HBO 1002 W/CEL	Shipping carton box 1	330 mm x 110 mm x 115 mm	4.17 dm ³	764.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.