

# **HBO 2700 W/CIL**

 $\label{thm:continuous} \mbox{HBO-IC Microlithography lamps for Canon $i$-line systems | Microlithography lamps for Canon $i$-line systems}$ 










# Product datasheet

# Technical data

### **Electrical data**

Nominal current	11000 A
Nominal voltage	260 V
Type of current	DC
Rated wattage	270000 W
Nominal wattage	270000 W

# Dimensions & weight



Diameter	620 mm
Length	3320 mm
Mounting length	332.0 mm
Length with base excl. base pins/connection	307.00 mm
Light center length (LCL)	149.1 mm <sup>1)</sup>
Electrode gap cold	5.0 mm

 $<sup>^{1)}</sup>$  Distance from end of base to tip of anode or cathode (cold)

## Additional product data

Base anode (standard designation)	SF33.5/50 <sup>1)</sup>		
Base cathode (standard designation)	SFa33.5-14/50 <sup>2)</sup>		
Product remark	Lamp contains overpressure even in cold status - additional safety regulations, supplied with the lamps, have to be fulfilled. Please read Technical bulletin DO-SEM TB 004 carefully		

<sup>1)</sup> With cable connection (M 8)

### **Capabilities**

	Forced <sup>1)</sup>
--	----------------------

<sup>2)</sup> With cable connection (M6)

# Product datasheet

Burning position	Other <sup>2)</sup>
<u> </u>	

 $<sup>^{1)}\,\</sup>mathrm{Maximum}$  permissible base temperature: 200 °C / Base cooling

## **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	05-03-2024		
Primary Article Identifier	4050300896588   4008321786838		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	65f8f183-407d-4000-b41f-fbefb99408fd   42d7a85e- dbe6-483f-9659-4d2b45293e9f		

<sup>2)</sup> Anode on top

### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321786838	HBO 2700 W/CIL	Folding carton box 1	- x - x -		
4008321786845	HBO 2700 W/CIL	Shipping carton box 4	800 mm x 600 mm x 825 mm	396.00 dm <sup>3</sup>	35051.00 g
4050300896588	HBO 2700 W/CIL	Shipping carton box	800 mm x 600 mm x 825 mm	396.00 dm <sup>3</sup>	1623.00 g
4050300896601	HBO 2700 W/CIL	Shipping carton box	- x - x -		
4050300586557	HBO 2700 W/CIL	Shipping carton box	800 mm x 600 mm x 825 mm	396.00 dm <sup>3</sup>	12242.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.