

ULTRA-VITALUX UV-A

Ultraviolet lamps



Areas of application

- Sunlight simulation
- Glue curing
- Artificial material aging
- Exposure of UV-sensitive photoresist coatings
- Terrariums
- Equine solaria

Product family features


- UV lamp for technical applications
- Direct operation without control gear







Product family datasheet



325755_ULTRA VITALUX

Product family datasheet

Technical data

Product description

ULTRA VITALUX 300 W 230 V E27

	Product informatio n	informatio				
Product description	Order reference	Nomin voltage		Construction voltage	Nomina wattago	
ULTRA VITALUX 300 W 230 V E27	U VITALX 300W 2	230 V	230 V	23000 V	30000	W 13.6 W
			Dimensions & v	veight	Lifespan	Additional product data
Product description	Radiated power 280315 nm (UVB)		Diameter	Length	Lifespan	Base (standard designation)
ULTRA VITALUX 300 W 230 V E27	3.0 W		1270 mm	1850 mm	1000 h	E27
	Capabilities		Environmental info	ormation ling Art. 33 of EU Regula	ition (EC) 19	907/2006

Product description	CAS No. of substance	Safe Use Instruction	Declaration No. in SCIP database
ULTRA VITALUX 300 W 230 V E27	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	bc3094dc-cc43- 4d18-80c6- c26db04e81b7

(REACh)

05-03-2024

Burning position

Any

Date of Declaration

Primary Article

4008321543929

Identifier

Candidate List

Substance 1

Lead

Product family datasheet

Safety advice

Due to their intense heat generation, the lamps may only be operated in suitable luminaires. The lamps must also be protected against moisture and splashing water. In case of improper use, UV radiation may lead to sunburn and conjunctivitis. Not approved for use on persons according to the new edition of EN 60335-2-27.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.