

HBO 16005 W/AU

HBO-IC Microlithography lamps for other LCD systems | Microlithography lamps for other LCD systems






April 25, 2024, 01:42:07 HBO 16005 W/AU

Technical data

Electrical data

Nominal voltage	147 V
Nominal current	109 A
Type of current	DC
Rated wattage	1600000 W
Nominal wattage	16000.00 W

Dimensions & weight



Diameter	1400 mm
Length	5500 mm
Mounting length	532.0 mm
Length with base excl. base pins/connection	515.00 mm
Light center length (LCL)	239.0 mm ¹⁾
Electrode gap cold	17.0 mm

 $^{1)}$ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFa46-35-14/70 ¹⁾
Base cathode (standard designation)	SFa40-35-12/85 ²⁾

 $^{1)}$ With cable connection (M 8)

 $^{\rm 2)}$ With cable connection (M10)

Capabilities

Cooling	Forced ¹⁾
Burning position	Other ²⁾

1) Maximum permissible base temperature: 200 °C $\,$

²⁾ Anode on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	06-03-2024		
Primary Article Identifier	4008321416452 4052899196933		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	f01f3d93-1e6c-4b0b-96d0-8fe9b97e53b6 d10604c9-a7f1-43d2-a2c3-d314bafbce6a		

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321416452	HBO 16005 W/AU	Shipping carton box 1	400 mm x 400 mm x 900 mm	144.00 dm ³	7144.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.