

Product family datasheetSubstiTUBE Advanced Ultra Output

LED tubes for electromagnetic control gears








Page 1 of 4

Product family datasheet

Technical data

	Electrical data			Photometrical data	Light technical data	Dimensions & weight	
Product description	Operating frequency	Claimed equiv. conventional lamp power	Nominal current	Light color (designation)	Beam angle	Overall length	Product weight
ST8AU-EM 1560 W/830 1200 mm	50/60 Hz	36 W	74 mA	Warm White	190 °	1212.00 mm	175.00 g
						ation Art. 33 of EU Regulation (EC) 1907/2006	
	Temperatures & operating conditions	Lifespan	Certificates & standard	ds	_		n (EC) 1907/2006
Product description	•	Lifespan Lumen maintenance at end of service life	Certificates & standard	ds Energy efficiency class	Information according		n (EC) 1907/2006 Declaration No. in SCIP database

Product family datasheet



ST8AU-EM 1560 W/830 1200 mm

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product code Product description Packaging unit (Pieces/Unit) Dimens	nsions (length x width x height) Volume	Gross weight
--	---	--------------

SubstiTUBE Advanced Ultra Output

Product family datasheet

Logistical Data

4058075611917	ST8AU-EM 1560 W/830 1200 mm	Shipping carton box 10	1352 mm x 210 mm x 115 mm	32.65 dm ³	2729.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany