

Product datasheet

ST8AU-EM 1560 W/830 1200 mm

SubstiTUBE Advanced Ultra Output | LED tubes for electromagnetic control gears



Product datasheet

Technical data

Electrical data

Operating frequency	50/60 Hz
Nominal current	74 mA
Claimed equiv. conventional lamp power	36 W

Photometrical data

Light color (designation)	Warm White
Luminous flux	2250 lm

Light technical data

Beam angle	190 °
------------	-------

Dimensions & weight



Product weight	175.00 g
Overall length	1212.00 mm

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Lifespan

Lumen maintenance at end of service life	0.7
--	-----

Additional product data

Appropriate disposal acc. to WEEE	Yes
Mercury content	0.0 mg

Certificates & standards

Product datasheet

Energy efficiency class	D
Energy consumption	16.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4058075611917
Declaration No. in SCIP database	In work

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075611917	ST8AU-EM 1560 W/830 1200 mm	Shipping carton box 10 Pieces Sleeves	1352 mm x 210 mm x 115 mm	32.65 dm ³	2729.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany