Product family datasheet



LEDriving BASIC P21/5W



Product family datasheet

Technical data

	Product info	Product information				Electrical data			
Product description	Order reference	Product type (off- road vs. on-road)	Application and Product		Power input	Nominal voltage	Nominal wattage		
LEDriving BASIC ≜ P21/5W	1357CW	CW Off-road ≙ Mainly used for P21/5W signal/ indicator applications			1.44 W	120 V	120 W		
		Photometrical data		Dimensions & weight			Capabilities		
Product description	Test voltage	Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Technology		
LEDriving BASIC ≜ P21/5W	13.5 V	85/25 lm	±20 %	2000 mm	2000 h	2000 h	LED		
	Information	-	rt. 33 of EU Regu			•			
Product description	Date of Dec	laration	Primary Article Identifier		didate List CAS stance 1 1		No. of substance		
LEDriving BASIC ≜ P21/5W	06-03-2024	06-03-2024		4052899414518 Lea 4052899414495 4052899427327 4052899463295 4052899463080		743	9-92-1		

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDriving BASIC ≜ P21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	fe6d71fd-c80e-400d- 8cc2-14ed29394294 1d480114-7d33- 4144-80cc- 0d5f7210d25e e9e1666a-1f1f-4c57- 897e-b5d1a43415ca 71710aae-de5e- 4bc7-9841- c54466748320 9bf3b981-7442- 439c-a86d- e513fc794734

Product family datasheet

Download Data

 File

 Brochures

 LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.