

LEDDriving BASIC T4W



Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDDriving BASIC \triangleq T4W	Mainly used for signal/ indicator/ interior applications	Off-road \triangleq T4W	3750CW	0.78 W	12 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDDriving BASIC \triangleq T4W	0 W	13.5 V	30 lm	$\pm 20\%$	9.5 mm

Product description	Diameter	Lifetime Data		Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan B3	Lifespan Tc	Technology	Primary article identifier
LEDDriving BASIC \triangleq T4W	9.5 mm	2000 hr	2000 hr	LED	4052899463271 4052899414617 4052899463066 4052899414655

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDDriving BASIC \triangleq T4W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9add2d47-cd43-47d0-90e8-b42553d559f6 aadf4566-2f5c-420c-940e-ab52c14c2128 dc70588f-5433-4c78-9a81-18450deb8f7c 4ed996ff-d5b8-4576-b168-a975922e67e5

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.