Product family datasheet



LEDriving BASIC T4W



Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	Product type (off- road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ T4W	Off-road ≙ T4W	Mainly used for signal/ indicator/ interior applications	3750CW	0.78 W	12 V

	Photometric Data			etric Data		Physical Attributes & Dimensions
Product description	Nominal wattage	Test voltage	Nominal flux	luminous	Luminous flux tolerance	Diameter
LEDriving BASIC ≜ T4W	0 W	13.5 V	30 lm		±20 %	9.5 mm
		Lifetime D	ata	Capabilities	Environmen Regulatory Information Information according Ai EU Regulation 1907/2006	rt. 33 of on (EC)
Product description	Diameter	Lifespan B3	Lifespan Tc	Technology	Primary arti	cle

4052899463066 | 4052899414655 **Product description** Candidate list CAS No. of substance Safe use instruction Declaration no. in SCIP database substance 1 1 7439-92-1 Lead The identification of 9add2d47-cd43the Candidate List 47d0-90e8substance is b42553d559f6 | sufficient to allow aadf4566-2f5c-420c-940e-ab52c14c2128 | safe use of the

2000 hr

2000 hr

LED

article.

4052899463271 | 4052899414617 |

> dc70588f-5433-4c78-9a81-18450deb8f7c | 4ed996ff-d5b8-4576b168-a975922e67e5

9.5 mm

Product family datasheet

Download Data

	File
*	User instruction GPRS_Safety symbols instructions
7	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.