OSRAM

LEDriving BASIC R5W



Product family datasheet

Technical data

	Product information		General Product Information		Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global referen		Power input	Nominal voltage
LEDriving BASIC ≙ R5W	Mainly used for signal/ indicator applications	Off-road ≙ R5W	5107C\	N	0.96 W	12 V
			Photome	etric Data		Physical Attributes & Dimensions
Product description	Nominal wattage	Test voltage	Nominal flux	luminous	Luminous flux tolerance	Diameter
LEDriving BASIC	0 W	13.5 V	55 lm		±20 %	19.0 mm
		Lifetime Data Capabilit		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Diameter	Lifespan B3	Lifespan Tc	Technology	Primary art	iicle
LEDriving BASIC ≜ R5W	19.0 mm	2000 hr	2000 hr	LED	405289946 405289946 405289946	L4556

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84- 49d2-aad6- 61ee9185fc4c a74edd59-fe84-466f- 9e9c-d76036657cbc 4deab8c0-c089- 4d6a-90f4- 3738f5af799e e8c7bd92-d6cb-4cf2- 9e8f-8360bae74918 eb08c6c5-5573- 4254-af17- 5f6a4f492b5f

4052899414532

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

