OSRAM

Lightbar FX250-CB

Higher luminosity for improved safety on the road





Combo Beam Combined beam of light



Lighting distance up to 320 metersImproved far and near field illumination



Beam angle 5°
Exceptionally focused beam angle

Product family datasheet



Increased brightness thanks to LED auxiliary lights for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX250-CB is an ECE-compliant LED auxiliary light that provides additional, far field illumination on dark roads. Even in poor visibility conditions or at dusk, the ten high-performance LEDs reach a light distance of up to 320 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The auxiliary automotive light can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads.An intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. With a beam angle of five degrees, oncoming vehicles are not needlessly blinded and the light is evenly distributed. Robust and durable thanks to superior craftsmanshipAs an LED auxiliary light, the LEDriving Lightbar FX250-CB has to withstand quite a bit. Its compact housing and extremely robust polycarbonate lens can do just that. The LED bar for automobiles can stand up to the most extreme weather and environmental conditions. What's more, the integrated driver and thermal management system ensure that the ten highperformance LEDs will not overheat. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan for the LED bar. Safe and flexible both on-road and off-roadIts variability gives the LEDriving Lightbar FX250-CB a flexible range of uses. The LED lights can be installed on cars, utility vehicles, recreational and 4x4 vehicles and agricultural vehicles. Thanks to their extreme luminosity, they are also ideal as LED working lights on off-road vehicles. The powerful 2700 lumen LED auxiliary light provides the highest optical efficiency for every application and an aesthetic, homogeneous light distribution.

Product family datasheet

Technical data

	Product in	Product information			Electrical data			
Product description	Order reference	Application and Produc	, , ,	Nominal voltage	Nominal wattage	Test voltage	Luminous flux	
Lightbar FX250-CB	LEDDL103 CB	LEDDL103- Additional high beam 12/24 V 30 W 13.5 V 2700 lm CB application						
	Lifespan	Capabilities	Environmental information Information according Art. Regulation (EC) 1907/2006		Art. 33 of EU			
Product description	Lifespan Tc	Technology	Commodit	y code	Date of De	claration	Primary Article Identifier	
Lightbar FX250-CB	5000 h	LED	85122000	900	06-03-202	4	4052899595354	

Product description	Candidate List Substance 1	CAS No. of substance	Safe Use Instruction	Declaration No. in SCIP database
Lightbar FX250-CB	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1efd6f45-d91e-402d- 8d98-01f73e6f1f81

Product family datasheet

Download Data

	File
乙	User instruction LEDriving
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application Working and Driving Lights Amarok Winter
D	Movie application LEDriving driving & working lights in application (EN)
	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	360 Degree Image LEDriving LIGHTBAR FX250-CB, LEDriving LIGHTBAR FX250-SP

Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairs

Precise terms and conditions at: www.osram.com/guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











