

LEDDriving SL P21/5W RED

Ideal replacement for any vehicle




Suitable for various vehicle exterior applications

Available in Red

Replaces conventional P21/5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference	7528DRP
Product type (off-road vs. on-road)	Off-road $\pm$ P21/5W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


Electrical data

Power input	1.61 / 0.575 W
Nominal voltage	12.0 V
Nominal wattage	1.40/0.40 W
Test voltage	13.5 V
Power input tolerance	$\pm$ 25 %

Photometrical data

Luminous flux	100/10 lm
Luminous flux tolerance	$\pm$ 10 %
Light color LED	Red

Dimensions & weight



Diameter	27.0 mm
Product weight	16.00 g
Length	52.5 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Additional product data

Base (standard designation)	BAY15d
-----------------------------	--------

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Country specific categorizations

Order reference	7528DRP
-----------------	---------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172151740 4062172401319
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	c811f6b4-522c-4ae4-b05c-1a7c56bdb77d

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151740	LEDDriving SL $\triangle$ P21/5W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm ³	44.00 g
4062172151757	LEDDriving SL $\triangle$ P21/5W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm ³	256.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Product datasheet

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.