

LEDDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | General Product Information | Electrical Data | |
|--------------------------------|-------------------------------------|--|-----------------------------|-----------------|-----------------|
| | Product type (off-road vs. on-road) | Application (Category and Product specific) | Global order reference | Power input | Nominal voltage |
| LEDriving SL \triangleq P21W | Off-road \triangleq P21W | Mainly used for signal/ indicator applications | 7506DWP | 1.8 W | 12 V |

| Product description | Nominal wattage | Test voltage | Photometric Data | | Physical Attributes & Dimensions |
|--------------------------------|-----------------|--------------|-----------------------|-------------------------|----------------------------------|
| | | | Nominal luminous flux | Luminous flux tolerance | Diameter |
| LEDriving SL \triangleq P21W | 1 W | 13.5 V | 160 lm | $\pm 25\%$ | 25.0 mm |

| Product description | Diameter | Lifetime Data | | Capabilities | Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|--------------------------------|----------|---------------|-------------|-------------------|--|
| | | Lifespan B3 | Lifespan Tc | Technology | Primary article identifier |
| LEDriving SL \triangleq P21W | 25.0 mm | 1500 hr | 4000 hr | LED ¹⁾ | 4062172348652 4062172152181 4062172401210 4062172408318 |

| Product description | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|--------------------------------|----------------------------|------------------------|--|--|
| LEDriving SL \triangleq P21W | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 4b523b49-273b-43fa-a900-dfef06fdea31 e75f732e-151e-4392-9807-f15711d460b4 cbc40782-6f5e-4a73-ad3f-4f03b28c1891 431a14a2-e6f5-451f-b379-4763b7bc7850 |

¹⁾ Light-emitting diode lamp

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.