Product family datasheet

LEDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White


Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



OSRAM

Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product information | | | | Electrical data | | | | |
|--------------------------------|--------------------|---|-------------------------------|--|--------------------------------|--------------------|--------------------|--|
| Product description | Order reference | Product type (off- road vs. on-road) | Application and Product | | Power input | Nominal voltage | Nominal wattage | |
| LEDriving SL ≙ P21W | 7506DWP | VP Off-road P21W Signal/ indicator applications | | 1.8 W 12.0 V 1.40 W | | | | |
| | | Photometri | cal data | Dimension & weight | | | Capabilities | |
| Product description | Test voltage | Luminous flux | Luminous flux tolerance | Diameter | Lifespar B3 | n Lifespan Tc | Technology | |
| LEDriving SL \triangleq P21W | 13.5 V | 160 lm | ±25 % | 25.0 mm | 1500 h | 4000 h | LED ¹⁾ | |
| | | ital informati according Ar | on t. 33 of EU Regu | lation (EC) 1 | 1907/2006 (| REACh) | | |
| Product description | Date of Dec | | | | ndidate List CA bstance 1 1 | | S No. of substance | |
| LEDriving SL ≏ P21W | 19-04-2024 | 19-04-2024 | | 4062172152181 Lea 4062172348652 4062172401210 4062172408318 | | d 7439-92-1 | | |
| Product description | Safe Use Ins | truction | Declaration No. | in | | | | |
| | Sale Use ins | | SCID database | | | | | |

| Product description | Safe Use Instruction | Declaration No. in SCIP database |
|---------------------|---|--|
| LEDriving SL ≙ P21W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | e75f732e-151e- 4392-9807- f15711d460b4 |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

File Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.