LEDriving SL P27/7W RED

Ideal replacement for any vehicle




Suitable for various vehicle exterior applications Available in Red

Replaces conventional P277W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference 3157DRP	
Product type (off-road vs. on-road) Off-road ≙ P27/7W	
Application (Category and Product specific) Mainly used for signal/ indicator applications	


Electrical data

Power input	1.8 W
Nominal voltage	12.0 V
Nominal wattage	1.70 W
Test voltage	13.5 V
Power input tolerance	±25 %

Photometrical data

Luminous flux	60/10 lm
Luminous flux tolerance	±25 %
Light color LED	Red

Dimensions & weight



Diameter	25.7 mm
Product weight	13.30 g
Length	49.0 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Additional product data

Base (standard designation)	W2.5x16q	
Capabilities		
Technology	LED ¹⁾	
¹⁾ Light-emitting diode lamp		
Country specific categorizations		
Order reference	3157DRP	

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	07-03-2024	
Primary Article Identifier	4062172151689 4062172401777 4062172401418	
Candidate List Substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration No. in SCIP database	a5c512b0-7fa2-4907-bc1f-816fe7f2d8ed	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151689	LEDriving SL ≙ P27/7W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm³	39.00 g
4062172151696	LEDriving SL ≙ P27/7W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm³	228.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
*	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

