Product family datasheet

LEDriving SL W21W/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White

Replaces conventional W21W5W lamps

Easy upgrade to LED technology with plug & play solutions



OSRAM

Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W21/5W

LEDriving SL W21W/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W21W/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product information | | | Electrical data | | |
|----------------------------------|---------------------|---|--|-----------------|--------------------|--------------------|
| Product description | Order reference | Product type (off- road vs. on-road) | Application (Category and Product specific) | Power input | Nominal voltage | Nominal wattage |
| LEDriving SL \triangleq W21/5W | 7515DWP | Off-road ≙ W21/5W | Mainly used for signal/ indicator applications | 2.7 W | 12.0 V | 1.90/0.40 W |

| | | Photometri | cal data | Dimensions & weight | Lifespan | | Capabilities |
|-----------------------|-----------------|------------------|-------------------------------|------------------------|----------------|----------------|-------------------|
| Product description | Test voltage | Luminous flux | Luminous flux tolerance | Diameter | Lifespan B3 | Lifespan Tc | Technology |
| LEDriving SL ≙ W21/5W | 13.5 V | 155/25 lm | ±25 % | 20.0 mm | 1500 h | 4000 h | LED ¹⁾ |

| | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|-----------------------|--|----------------------------------|-------------------------------|---------------------------|
| Product description | Date of Declaration | Primary Article Identifier | Candidate List Substance 1 | CAS No. of substance 1 |
| LEDriving SL ≙ W21/5W | 07-03-2024 | 4062172152266 4062172401494 | Lead | 7439-92-1 |

| Product description | Safe Use Instruction | Declaration No. in SCIP database |
|-----------------------|---|--|
| LEDriving SL ≙ W21/5W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 4746391f-7cf0-4291- a57a-5bc608210a87 |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

File

Download Data

7

Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.