OSRAM

NIGHT BREAKER H7-LED

OSRAM's first street-legal LED replacement lamp





OSRAM's first street-legal LED replacement lamp ¹⁾

See and be seen more clearly, for more safety on the road, especially at night



Up to 220% more brightness ²⁾

Cool White LED-Upgrade with color temperature close to daylight for specific car models



Up to 5 times more lifetime ³⁾

Environmentally friendly through longer durability and less garage shop visits and reduced energy

First NIGHT BREAKER LED

With NIGHT BREAKER H7-LED, OSRAM's first street legal¹⁾ LED replacement lamp is now on the market.

The plug-and-play solution offers drivers significant advantages: very high cool white color temperature of 6,000 Kelvin with up to 220% more brightness compared to the minimum requirements of ECE R112, up to 5 times longer lifespan compared to halogen lamps and an additional 50% less glare.

OSRAM offers related installation accessories for the LED lamps."



Technical data

| | Product inf | ormation | | | | | | | |
|----------------------|---|--------------------------------|---|---------------------------|---------------------------------|---------------------------|----------|---|--|
| Product description | Product leg 1 | Product legal advice 1 | | Product legal advice 2 | | Product legal advice 3 | | Application (Category and Product specific) | |
| NIGHT BREAKER H7 LED | 1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb- led | | 2) Compared to minimum ECE R112. On top with 50% less glare. | | 3) Compared to halogen lamps | | Low beam | | |
| | | General Product Information | | Data | | | | | |
| Product description | Global orde reference | Global order reference | | Nominal vo | oltage N | Nominal wa | ittage | Power input toleranc e | |
| NIGHT BREAKER H7 LED | 64210DWN | 64210DWNB | | 12 V | 1 | L9 W | | ±10 % | |
| | | Photometr | ic Data | | | | | | |
| Product description | Test voltage | | | Nominal luminous flux | | Color temperature | | Light color LED | |
| NIGHT BREAKER H7 LED | 13.2 V | ±10 % | 1500 | lm | 6000 K | | Cool v | vhite | |
| | Physical At | tributes & Di | imensions | | | | | | |
| Product description | Diameter | Diameter | | Diameter | | Product weight | | Lamp base | |
| NIGHT BREAKER H7 LED | 13.8 mm | | 13.8 mm | | 55.00 g | | PX26d | | |
| | | | Lifetime Data | | Capabilities | Certificat standard | | | |
| Product description | Length | | Lifespan | Lifespan | Technology | Standard | ls | | |
| | | | Тс | B3 | | | | | |

| | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | | |
|----------------------|---|----------------------------|---------------------------|---|--|--|
| Product description | Primary article identifier | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | | |
| NIGHT BREAKER H7 LED | 4062172155045 4062172314169 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | | |

| Product description | Declaration no. in SCIP database |
|----------------------|-------------------------------------|
| NIGHT BREAKER H7 LED | 32a042de-1012- |
| | 4426-8ae2- |
| | 66cf75bb2b80 |
| | 2bab2114-821b- |
| | 4a4e-b4cb- |
| | 1e375c2d1837 |

Download Data

| | File |
|---|---|
| * | User instruction VW POLO AW6 |
| 1 | User instruction NIGHT BREAKER LED |
| * | User instruction NIGHT BREAKER LED |
| * | User instruction GPRS_Safety symbols instructions |
| ₹ | User instruction NIGHT BREAKER LED (EN) |
| D | Movie application NIGHT BREAKER LED H7 Einbauvideo Golf 7 (DE) |
| D | Product movie LED Night Breaker H7 Installation Video BMW (DE) |
| | ref_pim_amsp_product360degreeimages NIGHT BREAKER H7-LED 64210DWNB |

Legal advice

1) Approved H7-LED headlamp. Only applies to the respective countries in which there is approval and the vehicle models and light functions currently listed in the compatibility list. For exact conditions see www.osram.com/nb-led2) compared to minimum ECE R112. On top with 50% less glare.3) compared to halogen lamps

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

