OSRAM

NIGHT BREAKER H7-LED

OSRAM's first street-legal LED replacement lamp





OSRAM's first street-legal LED replacement lamp 1)

See and be seen more clearly, for more safety on the road, especially at night



Up to 220% more brightness 2)

Cool White LED-Upgrade with color temperature close to daylight for specific car models



Up to 5 times more lifetime 3)

Environmentally friendly through longer durability and less garage shop visits and reduced energy

First NIGHT BREAKER LED

With NIGHT BREAKER H7-LED, OSRAM's first street legal1) LED replacement lamp is now on the market.The plug-andplay solution offers drivers significant advantages: very high cool white color temperature of 6,000 Kelvin with up to 220% more brightness compared to the minimum requirements of ECE R112, up to 5 times longer lifespan compared to halogen lamps and an additional 50% less glare.OSRAM offers related installation accessories for the LED lamps."



Technical data

| | Product inform | ation | | | | | | |
|----------------------|--|------------------|---|---------------------------------|---------------------------------|--|-------------------------------|---|
| Product description | Product legal advice 1 | | Product legal advice 2 | | Product legal advice 3 | | Order reference | Application (Category and Product specific) |
| NIGHT BREAKER H7 LED | 1)Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb- led | | 2) Compared to minimum ECE R112. On top with 50% less glare. | | 3) compared to halogen lamps | | 64210DWN B | Low beam |
| | Electrical data | | | | | | Photometrie | al data |
| Product description | Nominal voltag | • | ominal attage | Power input toleranc e | Test voltage | Power input | Luminous flux tolerance | Luminous flux |
| NIGHT BREAKER H7 LED | 12.0 V | 19 | .00 W | ±10 % | 13.2 V | 19 W | ±10 % | 1500 lm |
| | | | Dimen | sions & wei | ght | | Lifespan | |
| Product description | | ight color ED | Length | | oduct eight | Diameter | Lifespan B3 | Lifespan Tc |
| NIGHT BREAKER H7 LED | 6000 K C | ool white | 81.3 m | m 55 | 5.00 g | 13.8 mm | 1500 h | 2500 h |
| | Additional product data | Capabilitie | s Cert | ificates & s | tandards | Environmen information Information according EU Regulat 1907/2006 | n Art. 33 of ion (EC) | |
| Product description | Base (standard designation) | Technology | Standards | | | Date of Declaration | | |
| NIGHT BREAKER H7 LED | PX26d | LED | ABG | | | 07-03-202 | Λ | |

| Product description | Primary Article Identifier | Candidate List Substance 1 | CAS No. of substance 1 | Safe Use Instruction |
|----------------------|--|-------------------------------|---------------------------|---|
| NIGHT BREAKER H7 LED | 4062172155045 4062172296496 4062172314169 4062172183109 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |

| Product description | Declaration No. in SCIP database | |
|----------------------|-------------------------------------|--|
| NIGHT BREAKER H7 LED | 2bab2114-821b- | |
| | 4a4e-b4cb- | |
| | 1e375c2d1837 | |
| | 18337190-31cf- | |
| | 421b-a63c- | |
| | 3e8000b5ddfa | |
| | 4050c576-f784- | |
| | 4aed-bf1f- | |
| | 7a44a95b1d83 | |
| | 32a042de-1012- | |
| | 4426-8ae2- | |
| | 66cf75bb2b80 | |

Download Data

| | File |
|----|--|
| * | User instruction NIGHT BREAKER LED |
| ₹ | User instruction NIGHT BREAKER LED |
| 7 | User instruction VW POLO AW6 |
| 75 | User instruction NIGHT BREAKER LED (EN) |
| | 360 Degree Image NIGHT BREAKER H7-LED 64210DWNB |

Legal advice

1) Approved H7-LED headlamp. Only applies to the respective countries in which there is approval and the vehicle models and light functions currently listed in the compatibility list. For exact conditions see www.osram.com/nb-led

2) compared to minimum ECE R112. On top with 50% less glare.

3) compared to halogen lamps

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

42