

Product datasheet

ST8PRO-EM 6.7 W/840 600 mm

SubstiTUBE PRO EM | High performance LED tubes for electromagnetic control gears (CCG),
shatterproof



Technical data

Electrical data

Rated wattage	6.70 W
Operating frequency	50...60 Hz
Max. lamp no. on circuit break. 10 A (B)	141
Max. lamp no. on circuit break. 16 A (B)	225
Nominal wattage	6.70 W
Nominal voltage	220...240 V
Nominal current	0.032 A
Claimed equiv. conventional lamp power	18 W

Photometrical data

Standard deviation of color matching	≤5 sdc _m
Rated luminous flux	1100 lm
Nominal luminous flux	1100 lm
Rated color temperature	4000 K
Color rendering index Ra	83
Color temperature	4000 K
Light color (designation)	Cool White
Luminous flux	1100 lm
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	190 °
Starting time	< 0.5 s

Dimensions & weight



Product weight	100.00 g
----------------	----------

Product datasheet

Length	603.0 mm
Outer bulb	T8
Overall length	603.0 mm
Diameter	26.7 mm

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Lifespan

Nominal lamp life time	60000 h
Rated lamp life time	60000 h
Lumen maintenance at end of service life	0.70
Number of switching cycles	200000

Additional product data

Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075612150
Mercury content	0.0 mg
Mercury-free	Yes
Base (standard designation)	G13
Predecessor EAN	4058075454088

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy efficiency class	C
Energy consumption	7 kWh/1000h
Type of protection	IP20

Country specific categorizations

Order reference	ST8PRO-0.6M 6,7
-----------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	25-07-2022
Primary Article Identifier	4058075454088 4058075612150
Declaration No. in SCIP database	In work

Product datasheet

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany