

Product datasheet ST8PRO-EM 1030 W/840 9100 mm

SubstiTUBE PRO EM | High performance LED tubes for electromagnetic control gears (CCG), shatterproof







Product datasheet

Technical data

Electrical data

Operating frequency	5060 Hz
Nominal current	49 mA
Claimed equiv. conventional lamp power	30 W

Photometrical data

Light color (designation)	Cool White
Luminous flux	1700 lm

Light technical data

Beam angle	190 °

Dimensions & weight



Product weight	144.00 g
Overall length	908.00 mm

Temperatures & operating conditions

Ambient temperature range	-20+50 °C

Lifespan

Lumen maintenance at end of service life	0.7
--	-----

Additional product data

Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075612198
Mercury content	0.0 mg
Mercury-free	Yes

Product datasheet

Predecessor EAN	4058075454125

Certificates & standards

Energy efficiency class	С
Energy consumption	11.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 25-07-2022				
Primary Article Identifier	4058075454125 4058075612198			
Declaration No. in SCIP database	In work			

Equipment / Accessories

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075454125	ST8PRO-EM 1030 W/840 9100 mm	Shipping carton box 10 Pieces Sleeves	1048 mm x 210 mm x 115 mm	25.31 dm³	2298.00 g
4058075612198	ST8PRO-EM 1030 W/840 9100 mm	Shipping carton box 10 Pieces Sleeves	1048 mm x 210 mm x 115 mm	25.31 dm³	2298.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

⁻ Suitable for operation with low-loss and conventional control gears

Product datasheet

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany