

# **TYREinflate 2000**





Powerbank-Function Can be used to charge different electronic devices such as cell phones etc.



**LED-Light** High quality LED light for the display as well as for the flashlight function.



Digital & Auto Stop Digital backlit display and Auto Stop function when preset pressure is reached.



2-year-OSRAM guarantee\*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products.



#### Compact rechargeable tyre inflator

The OSRAM TYREinflate 2000 is a rechargeable tire pump with digital backlit display for easier and more accurate pressure measurements and inflation of tires that displays pressure values in BAR, kPA and PSI. The OSRAM TYREinflate 2000 has an internal memory and thanks to the memory function up to four different values for different tires can be programmed and stored. It is also equipped with an auto-stop function: the OSRAM TYREinflate 2000 stops automatically when the correct and preset pressure is reached. Through the included USB cable, the OSRAM TYREinflate 2000 is rechargeable, and no 12V outlet is required for power supply, so this is not only for inflating car tires, but can also be used for inflating bicycle, scooter and motorcycle tires. The lightweight and compact design of the OSRAM TYREinflate 2000 makes it ideal for onthe-go use and can be taken almost anywhere. With the included storage bag, simply store in the glove compartment of the car, a bag or rucksack. A bracket for mounting and storage on a bicycle is included. Thanks to the powerbankfunction, the OSRAM TYREinflate 2000 can also be used as a charger for electronic devices such as e.g. a mobile phone. In addition, the integrated flashlight function can provide illumination at night or in poor lighting conditions. Also included is a 2-piece adapter set that can be used as a connector for bikes, balls and other inflatables with Presta valves.OSRAM offers a 2-year guarantee\* on this product.\* for precise conditions please refer to: www.osram.com/amguarantee

#### Technical data

	Electrical data	Dimensio	ons & weight	eight		oroduct	Capabilitie s	
Product description	Nominal voltage	Height	Width	Length	Display Type	e	Fuse	
TYRE inflate 2000	3.7 V	170 mm	70.0 mm	70.0 mm	Digital		18 A	
	Country spe categorizati		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)					
Product description	Order refere	ence	Date of Declaration		Primary Article Identifier		Declaration No. in SCIP database	
TYRE inflate 2000	OTIR2000		07-03-2024	40621	72198769	In work		

#### Download Data

	File
∽	User instruction TYREinflate 2000
D	Movie application TYREinflate OTIR2000 How to Video (EN)

#### Safety advice

The product may reach a noise level of up to 83 dB

#### Legal advice

CE and EAC compliant

RoHS 2 201/65/EU and RoHS 3 2015/863

**REACH Declaration of Conformity** 

MSDS (for rechargeable batteries)

\* for precise conditions please refer to: www.osram.com/am-guarantee

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.