

# Connection Cable 300 DT AX



## 3-meter cable length

With a length of 3m, the cable is able to install appropriate lighting even on large vehicles



## Easy Installation

Specially designed to connect the LEDriving driving and working lights of the PX-, SX- and FX-Series to a power source



## Matrix Portfolio

A vehicle-specific lighting set-up can be put together individually. Mix & match. Vary and combine



## 2-year OSRAM Guarantee

OSRAM products are innovative and technologically high-quality products that are carefully tested and subject to the strict monitoring undertaken by the OSRAM quality assurance system



## Professional light for professional work

With the OSRAM LEDriving Professional Series PX working lights portfolio, it is now possible to find exactly the right lighting for a wide range of special professional tasks and applications. Additionally, they can be mounted in three different ways: Direct mounting, flexible standard mounting, and heavy-duty mounting. OSRAM has developed specially designed mounting kits and a cable with DT-connector. The LEDriving Connection Cable 300 DT AX is compatible with all OSRAM LEDriving working lights of the Professional Series PX and with the LEDriving driving and working lights of the SX- and FX- series. It is suitable for 12V and 24V vehicles and with the DT connector it can provide a quick and easy connection to a power source for setup of the LEDriving driving and working lights. The conductor material is made of pure copper and with a length of 3m the cable is able to install appropriate lighting even on large vehicles. OSRAM provides a 2-year guarantee on this product<sup>1)2)1)</sup> Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.<sup>2)</sup> For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Technical data

Product information

|   |                                     |
|---|-------------------------------------|
| Order reference                             | LEDPWL ACC 103                      |
| Application (Category and Product specific) | Working & Driving Light Application |

Electrical data

|                 |         |
|-----------------|---------|
| Nominal voltage | 12/24 V |
|-----------------|---------|

Dimensions & weight



|                |         |
|----------------|---------|
| Product weight | 24900 g |
| Length         | 3000 mm |

Lifespan

|           |         |
|-----------|---------|
| Guarantee | 2 years |
|-----------|---------|

Additional product data

|                   |              |
|-------------------|--------------|
| Connector to lamp | DT Connector |
|-------------------|--------------|

Certificates & standards

|           |            |
|-----------|------------|
| Standards | ROHS/REACH |
|-----------|------------|

Country specific categorizations

|                 |                |
|-----------------|----------------|
| Order reference | LEDPWL ACC 103 |
|-----------------|----------------|

Logistical data

|                |             |
|----------------|-------------|
| Commodity code | 73269098900 |
|----------------|-------------|

Environmental information

Product datasheet





| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
|---|---------------|
| Date of Declaration   | 23-02-2024    |
| Primary Article Identifier  | 4062172294805 |
| Declaration No. in SCIP database                                      | In work       |

Logistical Data

| Product code  | Product description                             | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume                | Gross weight |
|---------------|---|---------------------------------|---|-----------------------|--------------|
| 4062172294805 | Connection Cable<br>300 DT AX LEDPWL<br>ACC 103 | Folding carton box<br>1         | 98 mm x 66 mm x<br>227 mm               | 1.47 dm <sup>3</sup>  | 302.00 g     |
| 4062172294812 | Connection Cable<br>300 DT AX LEDPWL<br>ACC 103 | Shipping carton box<br>30       | 350 mm x 315 mm x<br>474 mm             | 52.26 dm <sup>3</sup> | 9850.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File  |  |
|---|--|
|  | User instruction<br>LEDriving PROFESSIONAL WORKING LIGHTS                            |
|  | Movie application<br>OSRAM Quality Testing LEDriving working and driving lights (EN) |
|  | Movie application<br>OSRAM LEDdriving and working lights Imagefilm (EN)              |
|  | Movie application<br>LEDriving Driving and Working Lights Reference Video (EN)       |

**Safety advice**

For detailed application information, please refer to the product data sheet and the user instruction

**Legal advice**

1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.

2)For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

**Application advice**

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM