OSRAM

LEDriving HL BRIGHT H13



Up to +300% more brightness

More light allows to see

farther and therefore react

sooner. Signs, obstacles and

hazards can be recognized sooner.Compared to minimum ECE R112




Very compact LED replacement for conventional H13 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



Cool White color temperature of 6,000 K





4 year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee





High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to www.osram.com/am-guarantee.The LEDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product info	Product information				Electrical data		
Product description	Order reference	Product type (off- road vs. on-road)	Application (Category and Product specific)		Power input	Nominal voltage	Nominal wattage	
LEDriving HL BRIGHT ≜ H13	9008DWBR T	Off-road ≙ H13	Mainly used for Low 15 / 10 12.0 V 10/15 W Beam, High Beam W and Fog light applications					
	Photometric	Photometrical data		Lifespan	Capabiliti	inform Inform accord EU Re		
Product description	Luminous flux	Luminous flux tolerance	Diameter	Lifespan Tc	Technolog	gy Date o	f Declaration	
LEDriving HL BRIGHT ≜ H13	1500/100 0 lm	±20 %	14.0 mm	5000 h	LED	08-03	-2024	

Product description	Primary Article	Declaration No. in
	Identifier	SCIP database
LEDriving HL BRIGHT ≙ H13	4062172316019	In work

Product family datasheet

Download Data

File



User instruction LEDriving HL BRIGHT



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











