

HMI 2500 W/SE XS

HMI Single-End Lamps (other) | Metal halide lamps, single-ended



Technical data


Electrical data

Nominal voltage	115 V
Nominal current	256 A
Lamp voltage	115 V
Nominal wattage	2500.00 W

Photometrical data

Nominal luminous flux	220000 lm
Color temperature	6000 K
Color rendering index Ra	90

Dimensions & weight



Diameter	60.0 mm
Length	225.0 mm
Light center length (LCL)	127.0 mm

Lifespan

Lifespan	500 h
----------	-------

Additional product data

Base (standard designation)	G38
-----------------------------	-----

Capabilities

Burning position	Any
------------------	-----

Certificates & standards

EEL – Energy Label	B
--------------------	---

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4050300284293 4050300932149 4008321281173 4062172350099
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300284293	OSRHMI2500SE	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300284293	HMI 2500 W/SE XS	Shipping carton box 1	160 mm x 160 mm x 375 mm	9.60 dm ³	548.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.