

LEDDriving HLM EASY H7/H18



Ultra compact LED replacement for conventional H7/H18 high and low beam lamps (2in1)

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation.



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system for motorcycles.

With its socket-based solution, the OSRAM LEDDriving HLM EASY retrofits provide an ultra-compact LED replacement of conventional H7/H18 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility. An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation. The LEDDriving HLM EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference	64210DWESY
Product type (off-road vs. on-road)	Off-road ≙ H7/H18
Application (Category and Product specific)	Mainly used for Low Beam, High Beam

Electrical data

Power input	16.0 W
Nominal voltage	12.0 V
Nominal wattage	16.00 W
Test voltage	13.2 V
Power input tolerance	±25 %

Photometrical data

Luminous flux	1400 lm
Luminous flux tolerance	±25 %
Color temperature	6500 K
Light color LED	Cool white

Dimensions & weight

Length	58.0 mm
Diameter	20.0 mm
Product weight	21.00 g

Lifespan

Lifespan Tc	1000 h
-------------	--------

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	64210DWESY
-----------------	------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	08-03-2024
Primary Article Identifier	4062172321501 4062172399845

Product datasheet

Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	c27fc65c-c089-4c9e-8ffc-822db682f4c2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172321501	LEDiving HLM EASY ≙ H7/H18	Blister 1	135 mm x 95 mm x 35 mm	0.45 dm ³	32.00 g
4062172321518	LEDiving HLM EASY ≙ H7/H18	Shipping carton box 5	154 mm x 113 mm x 145 mm	2.52 dm ³	261.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

