Product datasheet

LEDinspect WIRE-FREE SLIM 600

Wire-Free charging compatible
Simply place on the Wire-Free charging pad to securely hold and recharge

Slim design
Easily place bright 600 Lumens white light where you need it most

Built to last
IK08 and IP54 rated to survive the rigors of the professional workshop

The easiest way to recharge inspection lights

Inspection lights are a vital part of any professional's toolbox. Removing the need to find and plug into the correct charging cable, OSRAM's wire-free inspection lights recharge without hassle by simply being placed on the magnetic charging pad. This innovative design not only enhances convenience but also supports an uninterrupted workflow.

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights

General Product Information

Global order reference	LEDIL422

Electrical Data

Nominal wattage	5 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	5700 K
Nominal luminous flux	600 lm
Light color LED	White

Physical Attributes & Dimensions



Product weight	240.00 g
Length	325.0 mm
Width	43.0 mm
Height	37.0 mm

Lifetime Data

Guarantee	2 years

Capabilities

Technology	LED

© 2026, OSRAM GmbH. All rights reserved.

Certificates & standards

Standards	CE / EMC / MSDS / ROHS

Logistical data

Watt hour per battery	9.20

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	39eac002-3892-45bc-922c-294d6f9430fb

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172393140	INSPECTION LAMP	Folding carton box 1	65 mm x 46 mm x 182 mm	0.54 dm^3	595.00 g
4062172393157	INSPECTION LAMP	Shipping carton box 6	160 mm x 150 mm x 210 mm	5.04 dm^3	6170.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	User instruction LEDinspect WIRE-FREE SLIM 600
	User instruction GPRS_Safety symbols instructions

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.

© 2026, OSRAM GmbH. All rights reserved.